PS-EUROPE
INFRAROTHEIZUNG

PS-europe Inh. Gerhard Birner
GSA: 33567778; EORI #: ATEOS1000150918; GLN: 911 00 302 88 383
Rossakgasse 8/B205, AT-1230 Wien
www.ps-europe.eu

EC - Declaration of Conformity

The devices listed in the table are the subject of the declaration and comply with the relevant harmonization legislation of the European Union:

Directive 2014/35/EU (Low Voltage Directive)
Directive 2014/30/EU (EMC Directive on Electromagnetic Compatibility)
Directive 2011/65/EU including amending Directive (EU) 2015/863 (RoHS Directive)
Directive 2009/125/EC (Ecodesign Directive) in conjunction with Regulation (EU) 2015/1188

Harmonised standards applied

With reference to the standards for which conformity is declared:

Safety (low voltage):
EN 60335-1 (Safety of Household Electrical Appliances)
EN 60335-2-30 (Particular requirements for space heaters)
EN 62233 (Electromagnetic fields of household appliances with regard to the safety of persons)

Electromagnetic compatibility (EMC):
EN 55014-1 (Interference emission)
EN 55014-2 (Immunity)
EN 61000-3-2 (harmonic currents)
EN 61000-3-3 (voltage changes/flicker)

Restriction of Hazardous Substances (RoHS):
EN IEC 63000 (Technical documentation for the assessment of electrical and electronic equipment with regard to the restriction of hazardous substances)

Device specifications	
Body:	Solid steel body fully powder coated with a smooth surface.
Color:	Standard white (RAL 9003), or colored option at the fresh line
Surface temperature:	electronic adjustable average temperature by 85 to 115°C at 230Volt, max. 120°C
Montage:	Wall mount, without screws and dowels
heating cable:	Steelcord in thermally conductive potting compound
Certificates:	IP 54, CE certified, TUV common specifications for infrared heating panels were adhered to.
Warranty:	15 Years
The place of production:	Made in Austria
recycled content:	PCR 91%
PFAS-Free Declaration	Yes
reduced packaging	The packaging is cardboard and the PE-materials inside are 100% recyclable.

DELUXE TD devices	power in Watt	Ampere	weight in kg	device in cm			depth incl. braket in cm	Power cord in m	M-set	Box dimensions in cm			Box weight
	230V/50Hz			wide	lenght	hight				wide	lenght	hight	In kg
DELUXE TD 230	230	1,00	6,5	52	32	1,9	4,2	1,9	L15	57	37	8	0,3
DELUXE TD 330	330	1,43	9,0	60	40	1,9	4,2	1,9	V15	65	45	8	0,4
DELUXE TD 530	530	2,30	10,0	60	60	1,9	4,2	1,9	V25	65	65	8	0,5
DELUXE TD 600	600	2,61	11,0	80	50	1,9	4,2	1,9	V35	85	55	8	0,7
DELUXE TD 660	660	2,87	12,0	150	32	1,9	4,2	1,9	L35	155	37	8	0,7
DELUXE TD 750	750	3,26	12,5	100	50	1,9	4,2	1,9	V45	105	55	8	0,8
DELUXE TD 820	820	3,57	13,5	89,2	59,2	1,9	4,2	1,9	L45	95	65	8	0,9
DELUXE TD 950	950	4,13	14,5	100	60	1,9	4,2	1,9	V55	105	65	8	1,0
DELUXE TD 1000	1000	4,35	16,0	110	60	1,9	4,2	1,9	V65	115	65	8	1,1
DELUXE TD 1100	1100	4,78	19,5	119,5	59,2	1,9	4,2	1,9	L55	125	65	8	1,2
DELUXE TD 1300	1300	5,65	23,5	150	59,2	1,9	4,2	1,9	L65	155	65	8	1,4
DELUXE TD 1350	1350	5,87	23,5	100	90	1,9	4,2	1,9	V85	105	95	8	1,4

PSE-Austria
Inh. Ing. Mst. Gerhard Birner
Rossakgasse 8/B205, 1230 Wien;
M: info@pse-austria.at; W:pse-austria.at
T: +43 676 [illegible] 8893; UID: ATU [illegible]69
GSA: 33567778; EORI: ATEOS1000150918

technical inspection means
Inh. Ing. Mst. Gerhard Birner

Vienna, 01.07.2026
Local / Date: